

OnAlert® Text Display

Emergency Notification Accessory

The Warning Systems, Inc (WSI) Text Display is an accessory specifically designed to work with the WSI UHF and VHF OnAlert® radios. It can receive up to 80 characters of text allowing the sender to create custom messages or use those that accompany their custom prerecorded wav files. The Text Display, like the TAR and Strobe, is battery backed allowing it to operate when AC power is down or unavailable. The backlit display makes it visible in dark environments. The OnAlert Text Display Accessory coupled with the WSI Tone Alert Radio can be used to notify those who are hearing impaired or recipients in high noise environments. Since 1998, thousands of these accessories have been sold to provide instructional information to users.

Some of the Text Display's beneficial features include:

- Easily interfaced to an OnAlert Tone Alert Radio (TAR) through the unit's RJ-12 jack
- Emergency notification provided to those who are hearing impaired or recipients in high noise environments via the 80 character LCD screen
- Highly visible in darkness; back-lit display is automated to conserve power and maximize use via internal batteries during prolonged power outages
- Expandable design allows combinations of up to six total Strobes and Text Displays to be used with one OnAlert TAR allowing up to 600 feet of coverage
- Internal lead-acid (gel cell) batteries for backup power in situations where commercial power is interrupted
- Compliant with Americans with Disabilities Act (ADA) and Chemical Stockpile Emergency Preparedness Program (CSEPP) requirements
- Wall mountable for better visibility in certain areas



Specifications

- *LCD Display Size: 1 x 3 inches, 4 lines with 20 characters per line*
- *Character Matrix Size: 5 x 7 pixel*
- *Color: Blue characters on easy-view yellow-green background*
- *Backlight: Yellow-green*
- *Daisy Chain Cable / Plug: RJ-12 plugs, standard telephone-type cable utilized*
- *Primary Power Source 117 VAC, 60 Hz wall plug DC power supply, UL/CSA Listed*
- *Backup Power Source: Internal, dual 6V, 4AH trickle-recharged lead-acid batteries (with dynamic deep discharge prevention)*
- *Mechanical Size: 6" W x 4½" H x 7½" D*
- *Mechanical Weight: 6 pounds*
- *Operating Temperature Range: -20° to +50° C (-4° to +122°F)*



Warning Systems, Inc.
www.warningsystems.com
Email: sales@warningsystems.com
Phone: 256-880-8702 ext. 115
Fax: 256-880-8785